

Technical Data

Build envelope	mm	249.6 x 140.4 x 240
	in	9.83 x 5.53 x 9.45
Printing speed	mm/hr	20 (0.1 mm/layer)
Accuracy	μm	±50 (>80%)
Elevator positioning accuracy	μm	≤±3
Layer thickness	mm	0.05 / 0.1
Resolution		3840 x 2160
Light source		UV LED
Optical power	W	4 (typical)
Pixel size	μm/pix	65
Wavelength	nm	405
Customer input file format		stl / .obj / .off / .ply / .3mf
Data pre-processing		Polydevs Pro / DLP
Printer controlling		DSCON
Operating system		Windows 10
Touch screen size		10.1
Data transfer interface	in	USB / Ethernet
Power supply		110 / 220 VAC, 50 / 60 Hz
Rated power	w	800
Temperature range	°C / °F	22-26 / 72-79
Max temperature change rate	°C/hr	1
Relative humidity	%	<40
Printer size unpacked	mm	600 x 510 x 1450
Printer weight unpacked	kg	122
CE certificate		Yes



UnionTech

Shanghai Union Technology Corporation
 Room 102, Unit 40, 258 Xinzhuang Rd, Shanghai, 201612, China
 enquiry@uniontech3d.cn Tel: +86-021-64978786
 www.uniontech3d.com

UnionTech GmbH
 Regus Berliner Carree, Berliner Allee 47, 64295 Darmstadt, Germany
 info@uniontech3d.de Tel: +49 (0) 6151-2776067
 www.uniontech3d.de